

General Specifications

- Aeronautic quality precision Cr-Moly tube manufactured by par Osborn Metals.
- Seamless cold drawn and stress relieved tube
- Good bending performance, good weld ability and very good toughness and consistency
- More than meets:
 - EN10305-1 / 25CrMo4+SR – 1.7218+SR
- Can substitute to
 - 4130 Cond N (AMS6360, Mil T 6736, ASTM A519)

Applications

- These tubes are adapted to motorsport and more generally to all domains requesting high performances and quality.
- Examples of use cases :
 - Roll cages
 - Anti-roll bars
 - Steering columns
 - Struts

Material Spec & Norms

- 25CD4S Aerospace quality
- Cleanliness Class2/AIR0819 & BS S100
- Chemical composition WL W.-Nr. 1.7214
- Tolerances acc. to EN10305-1 (or better on demand)

Mechanical Characteristics

- Tensile strength: $R_m \geq 750 \text{ MPa}$
- Yield strength: $R_{p0,2\%} \geq 650 \text{ MPa}$
- Elongation: $A\% \geq 15 \%$
- Usual bending capability: $R_{mini} = 3 * \varnothing^*$
- * Can vary depending on diameter & thickness

	C	Si	Mn	S	P	Cr	Ni	Mo
Min	0,22	0,15	0,50	$\leq 0,015$	$\leq 0,020$	0,90	$\leq 0,30$	0,15
Max	0,29	0,25	0,80			1,20		0,25

Specificities

- 100 % Defect inspection by Eddy current testing
- Tubes are marked on the O/D as :
 - GT750-30x2-PV B21/155
- Tubes are delivered descaled, phosphatized and oiled
- Guaranteed full traceability

Options

- GT750 is delivered cold drawn and stress relieved (+SR). On demand, Osborn Metals can manufacture all dimensions in 25CrMo4 in different conditions: +C,+LC, +N, +A, +QT
- Linished & oiled