


General Specifications

- Hexagonal precision tubes
- Seamless cold drawn tubes
- The hexagonal tubes are delivered with minimum of quantity from 50kg to 500kg depending on the tubes.
- Dimensions go from 4mm to 38mm (inside length) most of the tubes are hold on stock.

Material Spec & Norms

- Tubes are delivered acc EN10305-1
- The material spec is C35E
- The tubes are typically delivered in +LC (light cold drawn)
- Other dimensions, other shapes (Hex in round, round in hex but also square, triangle...) as other material specs are possible on demand with a special manufacturing.



Applications

- These tubes are mostly used for hand tools
- Examples of use cases
 - Wrenches
 - Other hand tools

Catalogue

| int (mm) | tol | ext (mm) | tol | g/m |
|----------|-------------|----------|---------|-------|
| 4 | +0,10/+0,30 | 6,4 | +/- 0,2 | 156 |
| 5 | +0,10/+0,30 | 7,5 | +/- 0,2 | 195 |
| 5,5 | +0,10/+0,30 | 8,1 | +/- 0,2 | 221 |
| 6 | +0,10/+0,30 | 8,8 | +/- 0,2 | 261 |
| 7 | +0,10/+0,30 | 9,9 | +/- 0,2 | 296 |
| 8 | +0,10/+0,30 | 11,0 | +/- 0,2 | 345 |
| 9 | +0,10/+0,30 | 12,2 | +/- 0,2 | 430 |
| 10 | +0,10/+0,30 | 13,4 | +/- 0,2 | 510 |
| 11 | +0,10/+0,35 | 14,6 | +/- 0,2 | 590 |
| 12 | +0,10/+0,35 | 15,8 | +/- 0,2 | 680 |
| 13 | +0,10/+0,35 | 17,0 | +/- 0,2 | 760 |
| 14 | +0,15/+0,40 | 18,0 | +/- 0,2 | 830 |
| 15 | +0,15/+0,40 | 19,4 | +/- 0,2 | 993 |
| 16 | +0,15/+0,40 | 20,4 | +/- 0,2 | 1 020 |
| 17 | +0,15/+0,40 | 21,4 | +/- 0,2 | 1 075 |
| 18 | +0,15/+0,40 | 22,7 | +/- 0,2 | 1 220 |
| 19 | +0,20/+0,50 | 23,9 | +/- 0,2 | 1 320 |
| 20 | +0,20/+0,50 | 24,9 | +/- 0,2 | 1 440 |
| 21 | +0,20/+0,50 | 26,1 | +/- 0,2 | 1 500 |
| 22 | +0,20/+0,50 | 27,1 | +/- 0,2 | 1 575 |
| 23 | +0,20/+0,50 | 28,1 | +/- 0,2 | 1 640 |
| 24 | +0,20/+0,50 | 29,3 | +/- 0,2 | 1 785 |
| 25 | +0,20/+0,50 | 30,5 | +/- 0,2 | 1 935 |
| 26 | +0,25/+0,60 | 31,5 | +/- 0,2 | 2 040 |
| 27 | +0,25/+0,60 | 32,7 | +/- 0,2 | 2 160 |
| 28 | +0,25/+0,60 | 33,9 | +/- 0,2 | 2 320 |
| 29 | +0,25/+0,60 | 35,1 | +/- 0,2 | 2 490 |
| 30 | +0,25/+0,60 | 36,1 | +/- 0,2 | 2 575 |
| 32 | +0,25/+0,60 | 38,3 | +/- 0,2 | 2 830 |
| 35 | +0,3/+0,65 | 41,8 | +/- 0,2 | 3 350 |
| 38 | +0,3/+0,65 | 45,4 | +/- 0,2 | 3 980 |